



Imperial dimensions and weights per metre per ASTM A 269 or ASTM A 511

 OD in	Wall thickness, in												
	0.02	0.022	0.028	0.035	0.036	0.048	0.064	0.08	0.104	0.125	0.188	0.25	0.375
	 Weight, kg/m (conventional weights)												
1/8	0.034	0.037	0.044		0.052								
3/16		0.059	0.072		0.088	0.109							
1/4	0.075	0.081	0.101		0.125	0.157	0.193						
5/16			0.129		0.161	0.206	0.258						
3/8			0.157		1.2	0.254	0.323	0.383		0.507			
7/16					0.234		0.525						
1/2			0.214	0.264	0.273	0.352	0.452	0.545		0.76			
5/8					0.344	0.449	0.582	0.714		1.01			
3/4					0.417	0.546	0.712	0.869	1.09	1.27	1.71		
7/8						0.643	0.841	1.03		1.52			
1					0.563	0.741	0.971	1.19	1.51	1.77	2.48	3.04	3.8
1 1/8							0.838	1.1					
1 1/4							0.944	1.23	1.52		2.28		
1 3/8					0.781			1.36					
1 1/2					0.854			1.49	1.84		2.79	4	5.07
1 5/8								1.62					
1 3/4							1.32	1.75			3.29		
2								2.01			3.8		7.09
2 1/4											4.31		8.11
2 1/2								2.53			4.81		9.12
2 3/4								2.79					
3								3.05	3.79		5.83		11.1
3 1/2													13.2
4											7.85		15.2
5													19.4
6													23.5

Notes:

For austenitic stainless steels multiply the quoted weight by 1.014. For ferritic and martensitic steels multiply the quoted weight by 0.985.