

Rigid Coupling

Nominal Size mm/in	Pipe O.D mm/in	Dimensions			Bolt inch/mm	Working pressure Psi
		ΦD mm	L mm	H mm		
25	33.7	55	97	45	3/8×1-1/2 (M10×40)	300
1	1.327					
32	42.4	63.5	107.5	45	3/8×1-3/4 (M10×45)	
1 1/4	1.669					
40	48.3	69	114	45	3/8×2-1/8 (M10×55)	
1 1/2	1.9					
50	57	83.6	124	46	3/8×2-5/8 (M12×65)	
2	2.244					
50	60.3	83.6	124	46	1/2×2-5/8 (M12×65)	
2	2.375					
65	73	98	137	46	1/2×2-5/8 (M12×65)	
2 1/2	2.875					
65	76.1	98	139	46	1/2×2-5/8 (M12×65)	
2 1/2	3					
80	88.9	114	156	46	1/2×2-5/8 (M12×65)	
3	3.5					
100	108	138	186	50	1/2×2-5/8 (M12×65)	
4	4.25					
100	114.3	142	189	50	1/2×2-5/8 (M12×65)	
4	4.5					
125	133	164	213	50	1/2×2-5/8 (M12×65)	
5	5.25					
125	139.7	170	222	50	1/2×2-5/8 (M12×65)	
5	5.5					
125	141.3	170	218	50	1/2×2-5/8 (M12×65)	
5	5.563					
150	159	192	244	50	1/2×2-5/8 (M12×65)	
6	6.25					
150	165.1	196	244	50	1/2×2-5/8 (M12×65)	
6	6.5					
150	168.3	198	251	50	1/2×2-5/8 (M12×65)	
6	6.625					
200	216.3	254	340	62	3/4×3-1/2 (M20×90)	
8	8.515					
200	219.1	256	316	60	5/8×3-1/8 (M16×80)	
8	8.625					
250	267.4	313	400	64	3/4×3-1/2 (M20×90)	
10	10.527					
250	273	319	393	64	3/4×3-1/2 (M20×90)	
10	10.75					
300	318.5	368	464	64	7/8×4-1/3 (M22×110)	
12	12.539					
300	323.9	374	453	65	3/4×4-1/3 (M20×110)	
12	12.75					

